

IP66 防水防塵・屋外用高輝度モニター SD308-S-DS

VISUAL PRESENTATION



32インチ～86インチ FHD UHD
輝度2000nit～3500nit
使用環境温度 -30℃～80℃

IP66 OUTDOOR WATERPROOF KIOSK

- ✓ Super-slim design 98mm
- ✓ High Brightness 2000 nits~3500 nits
- ✓ 32"~65"
- ✓ AR anti-reflective glass
- ✓ IP66 and IK10 protection
- ✓ QLED technology
- ✓ Ultra-narrow frame 38mm
- ✓ Resistant to high temperature up to 110 °C
- ✓ Intelligent light sensor, low power consumption
- ✓ Support wall-mounted, hanging, and floor standing

SD STARVISUAL
DISPLAY



- ・ FHD又はUHDパネルの選択が可能です
- ・ 32/43/49/55/65/75/86インチまでのラインナップ
- ・ 使用環境温度は-30℃～80℃
- ・ アンドロイドプレーヤーが内蔵されます (FHD対応)
- ・ WindowsPCをオプションで内蔵できます
- ※ストレージ使用環境温度-30℃～55℃
- ・ オプションで3年保証あり
- ・ 液晶パネルはLG.高温対応IPSパネル
- ・ スタンドはオプションです
- ・ ベゼル幅 38mm 奥行98mm

国内販売
株式会社ファン・ファクトリー
〒192-0082 東京都八王子市東町5-5ハルズ八王子ビル8F
TEL 042-631-1316 FAX 042-631-1317
<http://www.funfactory.co.jp/>
planning@funfactory.co.jp



Model.No

SD308-S-DS

Panel	Display Size (inch)	32"	43"	49"	55"	65"	75"	86"	
	Resolution	1920x1080 (16:9)	1920x1080 (16:9)	1920x1080 (16:9)	1920x1080 (16:9)	1920x1080 (16:9)	3840x2160 (16:9)	3840x2160 (16:9)	
	Active Display Area (mm)	700.5(H) x394.8(V)	941(H)*530(V)	1073.5(H) x 603.0(V)	1209.6(H) x 680.4(V)	1428.5(H) x 803.5(V)	1650.3(H) x 928.3(V)	1938.2(H) x 1098.3(V)	
	Aspect Ratio	16:09	16:09	16:09	16:09	16:09	16:09	16:09	
	Brightness(cd/m2)	2000nit	2500nit	2500nit	3500nit	2000nits	2000 nits	00S	
	Contrast Ratio(Typ.)	3500:1							
	Viewing Angle(H/V)	178/178							
	Color	16.7M							
	Response Time(G-to-G)	6ms							
	Operation Hour	24/7							
Sound	Loud Speaker	5W, 8Ω (2sets)							
Power	Type	Internal							
	Power Supply	AC 100 - 240 V ~ (+/- 10 %), 50/60 Hz							
	Power Consumption	Max[W/h]	130W	180W	260W	300W	400W	600W	800W
		Sleep mode	less than 0.5W						
Off mode	less than 0.5W								
Mechanical Spec	Protection Glass	AR anti-reflection glass							
	Housing Lifetime	8 years							
	IP Rate	IP66							
	Anti-hazard Classification	IK10							
	Stand Type	Wall-mounted / Ceiling / Freestanding							
Environmental	Operating Temperature	-30°C - 80°C							
	Storage Temperature	-30°C - 55°C							
	Operating Humidity	10% - 80 %							
	Storage Humidity	5% - 98%							
	Cooling System	Powerful Turbofan & cross flow fan/Air condition (Optional)							
OS	Android Media Player	Processor	Rockchip® RK3288 (1.8GHz, Quad-core)						
		RAM	2G						
		Flash	8G EMMC						
		USB	USB2.0 HOST(X2)						
		LAN	10M/100M Ethernet(Network version screen only)						
		External memory	8GB SD card(up to 32G)						
		Multimedia	Video(MPG,AVI,MP4,RM,RMVB,TS),Audio(MP3,WMA),Image(JPG,GIF,BMP,PNG)						
		Media Resolution	1920*1080						
		Wi-Fi	802.11b/g/n Ethernet(Network version screen only)						
		Operating System	Android 7.1						
Certification	Safety	CE ROHS IP66							
Accessories	Included	Scheduling software, Remote control, Key, Power cable, SD card, Wall mount bracket							
	Quality assurance	1 year (2-3 years optional)							
	Type of packaging	Carton box /honeycomb box + wooden case							