

Product references	VEGA
Visual Pitch (mm)	0.93 mm
Pixel layout	Delta-Enhanced COB
LED chips per sqm	1.2M
Min viewing distance (m)	1.5 m
Max brightness after calibration (cd/m <sup>2</sup> )	3,000 cd/m <sup>2</sup>
Contrast (measured@500lux)	6,000:1
Viewing angles (H/V)	178°/178°
Color Space	95% UHDTV
Color Depth	12 bits / 68.7billions + 4 bits for High Dynamic Range
Color temperature	Adjustable - default 6,500K (D65)
LED matrix scan rate	2,600 Hz
Video refresh rate	600 Hz
Module size	216 x 108 mm
Serviceability	Front
Usage	Indoor
Lifetime @75% brightness	100,000h
IP Rating	Front side IP65 / Back side IP31
Operating Temp. range (°C)	-20/50°C
Storage Temperature range (°C)	-30/70°C
Operating Humidity	10-95%
Power cons. Avg (W/sqm)	170 W/sqm
Power cons. Max (W/sqm)	500 W/sqm
Certifications	UL60950 (# E487433) - CE

#### POWER SUPPLIES

Format	Rack 1U
Manufacturer	Meanwell RCP Series with rack RKP
Input	90 - 264 VAC 47-63 Hz
Max distance to display	100 m
Power distribution	Safe Extra Low Voltage 50V DC

#### VIDEO SERVER

Format	Rack 1U
Source compatibility	HDMI SDI up to 4Kp60 per input
Video source sync rate	Up to 60Hz
Max distance to display	+1 km with fiber-optics
Local Admin interface	Web based

#### REMOTE MONITORING

Admin interface	Ethernet
-----------------	----------

VISUAL PRESENTATION



●販売に関するお問合せ [国内]

**株式会社 ファン・ファクトリー**

〒192-0082 東京都八王子市東町5-5 ハルズ八王子ビル8階  
TEL : 042-631-1316 FAX : 042-631-1317  
URL : [www.funfactory.co.jp](http://www.funfactory.co.jp)

●販売に関するお問合せ [HK] : APT

URL : [www.auroraprojectteam.com](http://www.auroraprojectteam.com)

●製造メーカー : Deepsky

URL : [www.deepskycorp.com](http://www.deepskycorp.com)



**ENGAGE VIEWERS  
WITH BREATHTAKING  
DIGITAL DISPLAYS**